

Computational complexity in physics

Cristopher Moore

Computer Science Department and Department of Physics and Astronomy
University of New Mexico, Albuquerque NM 87131
and the Santa Fe Institute, Santa Fe, NM
`moore@cs.unm.edu`

February 1, 2008

There are many definitions of the word “complexity.” These fall into three main categories:

- Information and thermodynamic entropy, as in Shannon and Gibbs, with extensions by Crutchfield and others
- Minimum description length, as in Kolmogorov and Chaitin, and physical versions of this, as in Lloyd, Pagels and Gell-Mann
- Computational complexity.

More generally, computational complexity is about drawing qualitative distinctions between problems based on how hard it is to solve them. In a sense, computational complexity is descended from the concerns of the constructivists on hearing from Cantor that some infinities are bigger than others, e.g. that there are more subsets of the integers than there are integers. The constructivists denied that all subsets of the integers have mathematical existence, and insisted that we should only believe in those that have an effective description or definition [1]. As the 20th century progressed, this idea of a description came to mean an algorithm which could be carried out by some mechanical device, such as a Turing machine, to tell whether an integer is in the set or not. The Church-Turing thesis states that the Turing machine captures what is “computable” in any reasonable way, and this has been borne out by the fact that it is provably equivalent to lambda calculus, Boolean circuits, all known programming languages, and every physically reasonable computing device proposed to date.

As people actually started to build computers — as Turing’s ideas were joined with von Neumann’s — the question became not just whether a set or problem is computable or not, but whether it is *feasibly* computable, i.e. with a reasonable amount of memory and in a reasonable time. As computers got faster and people solved larger problems, the behavior of the computation time $f(n)$ in the limit of large problem size n became more and more important, causing us to adopt more and more conservative definitions of what we mean by feasible computation [2]. In the 1950’s, we asked how many nested exponentials it took to define f , in the 70’s and 80’s we asked whether f is polynomial or not, and as massively parallel computation becomes a reality we might demand that $f(n)$ be polylogarithmic, i.e. $\mathcal{O}(\log^k n)$ for some k , on a parallel computer with a polynomial number of processors.

This last class, the set of efficiently parallelizable problems, is called **NC**; it is believed to be a proper subset of **P**, the set of problems solvable in polynomial time. A problem is **P-complete** if it is among the hardest problems in **P**, in the sense that any other problem in **P** can be reduced to them. **P-complete** problems are believed to be *inherently sequential*, meaning that a polynomial amount of work has to be done step-by-step in order, and that even a massively parallel computer can’t improve on this very much — just as having 10 cooks doesn’t let you make dinner in 1/10 the time [3].

Note the analogy here to the distinction between chaotic systems, which have to be integrated numerically, and integrable ones, which can be predicted simply by plugging the initial conditions into a closed-form solution. For a chaotic system, the complexity of predicting the system for a time t in the future grows

linearly with t (or even quadratically, given the increasing accuracy we need at longer times) while for an integrable system this increases polylogarithmically with t (since t has $\mathcal{O}(\log t)$ digits that need to be manipulated, and we assume that we can evaluate the closed-form solution in time polynomial in the number of digits) or not at all.

In fact, we can classify a number of interesting physical systems based on whether the problem of predicting them is in **P** or **NC**. We can always predict a cellular automaton in polynomial time by simulating it explicitly, just as we can numerically integrate a differential equation. Moreover, since cellular automata can easily simulate Turing machines [4], this problem is **P**-complete in general. However, if the cellular automaton has certain algebraic properties, we can predict it much more quickly, in $\mathcal{O}(\log t)$ or $\mathcal{O}(\log^2 t)$ time. Thus in special cases the CA prediction problem can be in **NC**, even for some nonlinear rules [5, 6].

On the other hand, some systems such as lattice gases [7], sandpiles [8], and zero-temperature Ising dynamics [9] are **P**-complete to predict, meaning that unless **P** = **NC** (in which case all polynomial-time problems are efficiently parallelizable) there is no way around simulating them step-by-step. This is because these systems' dynamics allow us to build "gadgets" that carry information from place to place and manipulate it logically, so that predicting the system is equivalent to evaluating a Boolean circuit. Interestingly, our proof for sandpiles works in $d \geq 3$, and the complexity of sandpiles in two dimensions (which is the case relevant to self-organized criticality and conformal fields) remains an open question.

It is interesting to contemplate how this might be proved for systems like the Navier-Stokes equations; it seems impossible that there are short cuts for predicting hydrodynamics, but proving something like **P**-completeness for a system like this seems very distant. The reason is that the only known technique for proving computational hardness results is (essentially) to build a computer in the system, like the Boolean circuits mentioned above. Without a way to build a computer entirely out of water — whose only elements are the eddies and vortices themselves — we have no way to *prove* that the system is hard.

In fact, if **P** and **NC** are different it is known that there are problems in between, outside **NC** but not **P**-complete either. It may be that many physical systems lie in this gap, with neither a clever fast algorithm for predicting them without simulation, nor a way to build universal computers out of them. Unfortunately, if this is the case we have no idea how to prove that they are there.

An early application of computational complexity in physics was Barahona's proof that finding the ground state of a spin glass is **NP**-complete [10], meaning that it is as hard as optimization problems such as the Traveling Salesman's problem [11]. As far as we know, such problems take exponential time to search through the space of possible solutions.

Interestingly, two-dimensional spin glasses are in **P**, but adding even one layer makes them **NP**-complete. Since this presumably does not change their bulk properties, it is not clear how closely computational complexity is related to physical properties. The main difference is that computational complexity is a worst-case notion, while physics is concerned with the average case and bulk properties of a material in the thermodynamic limit. Some progress is being made in extending computational complexity to the average case [12], but this is difficult since one must choose a probability distribution for the notion of "average" to be meaningful, and it is not always clear what the most natural distribution is for a given problem.

In analogy to the random graphs of Erdős and Rényi, where we have a uniform distribution over all graphs with a given number of nodes and a given number of edges, we can construct random problem instances with a given number of variables and a given number of constraints. With this probability distribution, many **NP**-complete problems show a phase transition from satisfiability to unsatisfiability as we increase the number of constraints per variable beyond a critical threshold. This has become an active area of collaboration between computer scientists and physicists, including rigorous upper and lower bounds on these transitions using probabilistic arguments (e.g. [13], analysis of polynomial-time heuristics (e.g. [14]), and applications of the replica trick (e.g. [15]).

However, even for these phase transitions it is not clear to what extent computational complexity and thermodynamic properties are related. An early conjecture was that **NP**-complete problems have first-order phase transitions, while problems in **P** have second-order transitions. However, some **NP**-complete problems are easy on average, and in the random case behave like problems in **P**. For instance, 1-in-3 SAT is a variant of Satisfiability where we have triplets of literals, each of which is a variable or a negated variable, where we require exactly one literal in each triplet to be true. While 1-in-3 SAT is **NP**-complete, its phase transition is in the same universality class as that of 2-SAT, which is in **P**. This is because the **NP**-completeness is

buried under a simple percolation process, and with probability 1 the problem is satisfiable if and only if it is below the percolation threshold [16].

However, there does seem to be a connection between worst-case complexity and physical properties fairly often. For instance, Machta showed that predicting diffusion-limited aggregation is **P**-complete, since its dynamics can simulate a NOR gate [17, 18]. However, in the case of internal diffusion-limited aggregation, also known as diffusion-limited erosion, the dynamics are equivalent to a comparator gate, which unlike the NOR is incapable of generating arbitrary Boolean functions. This puts the worst-case complexity of IDLA in the (probably) lower complexity class **CC** $\subset$ **P**. In addition, a simple parallel algorithm seems to work in polylogarithmic time, much faster than explicit simulation, suggesting that predicting IDLA is in **NC** on average [19]. Physically, this seems to correspond to the fact that DLA grows complex, dendritic clusters, while IDLA clusters are spherical with logarithmic fluctuations. This example suggests that computational complexity really does say something about the dynamics of a system, and how those dynamics allow it to propagate information and enforce constraints between its degrees of freedom.

Acknowledgments. I am extremely grateful to Joseph McCauley, Arne Skjeltorp, and the organizers of the NATO School on Complexity and Large Deviations for inviting me to speak in Geilo.

References

- [1] P. Odifreddi, *Classical Recursion Theory*. Elsevier, 1989.
- [2] C.H. Papadimitriou, *Computational Complexity*. Addison-Wesley, 1994.
- [3] R. Greenlaw, H.J. Hoover, and W.L. Ruzzo, *Limits to Parallel Computation: P-Completeness Theory*. Oxford University Press, 1995.
- [4] K. Lindgren and M.G. Nordahl, “Universal Computation in Simple One-Dimensional Cellular Automata.” *Complex Systems* **4** (1990) 299–318.
- [5] C. Moore, “Quasi-linear cellular automata.” *Physica D* **103** (1997) 100–132.
- [6] C. Moore, “Predicting non-linear cellular automata quickly by decomposing them into linear ones.” *Physica D* **111** (1998) 27–41.
- [7] C. Moore and M.G. Nordahl, “Predicting lattice gases is P-complete.” Santa Fe Institute Working Paper 97-04-034.
- [8] C. Moore and M. Nilsson, “The computational complexity of sandpiles.” *Journal of Statistical Physics* **96** (1999) 205–224.
- [9] C. Moore, “Majority-vote cellular automata, Ising dynamics, and P-completeness.” *Journal of Statistical Physics* **88** (1997) 795–805.
- [10] F. Barahona, “On the computational complexity of Ising spin glass models.” *J. Phys. A* **15** (1982) 3241–3253.
- [11] M.R. Garey and D.S. Johnson, *Computers and Intractability: A Guide to the Theory of NP-Completeness*. W.H. Freeman, 1979.
- [12] Average-Case Complexity Forum, <http://www.uncg.edu/mat/avg/>
- [13] O. Dubois et al., “Typical random 3-SAT formulae and the satisfiability threshold.” *Proc. 11th Symp. on Discrete Algorithms* (2000) 126–127.
- [14] D. Achlioptas and G.B. Sorkin, “Optimal myopic algorithms for random 3-SAT.” *Proc. Foundations of Computer Science* (2000) 590–600.
- [15] R. Monasson et al., “Determining computational complexity from characteristic phase transitions.” *Nature* **400** (1999) 133–137.

- [16] D. Achlioptas, A. Chtcherba, G. Istrate, and C. Moore, “The phase transition in 1-in- k SAT and NAE 3-SAT.” *Proc. 12th Symp. on Discrete Algorithms* (2001) 721–722.
- [17] J. Machta, “The computational complexity of pattern formation.” *Journal of Statistical Physics* **70** (1993) 949.
- [18] J. Machta and R. Greenlaw, “The computational complexity of generating random fractals.” *Journal of Statistical Physics* **82** (1996) 1299.
- [19] C. Moore and J. Machta, “Internal diffusion-limited aggregation: parallel algorithms and complexity.” *Journal of Statistical Physics* **99** (2000) 629–660.